



CBL-500C 自润滑止推垫片标准公制尺寸
 CBL-500C CBLif-lubricating Thrust Washer Standard Metric Size



单位Unit: mm

| 型号规格 Standard No. | φ d | φ D | T ⁰ _{-0.10} | 螺孔 Bolt Hole | | | | | |
|----------------------|-------|-----|---------------------------------|------------------|-------------------|------------------|-------------------|----|---|
| | | | | φ D ₁ | 平头螺钉 Crop Bolt | φ d ₁ | 孔数 Bore Number | | |
| CBL-500C-10 | 10.2 | 30 | 3 | 20 | M3 | 3.5 | 2 | | |
| CBL-500C-12 | 12.2 | 40 | | 28 | | | | | |
| CBL-500C-13 | 13.2 | | | | | | | | |
| CBL-500C-14 | 14.2 | | | | | | | | |
| CBL-500C-15 | 15.2 | 50 | | 35 | | | | M5 | 6 |
| CBL-500C-16 | 16.2 | | | | | | | | |
| CBL-500C-18 | 18.2 | | | | | | | | |
| CBL-500C-20 | 20.2 | | | | | | | | |
| CBL-500C-25 | 25.2 | 55 | 5 | 40 | M6 | 7 | | | |
| CBL-500C-30 | 30.2 | 60 | | 45 | | | | | |
| CBL-500C-35 | 35.2 | 70 | | 50 | | | | | |
| CBL-500C-40 | 40.2 | 80 | 7 | 60 | M8 | 9 | | | |
| CBL-500C-45 | 45.3 | 90 | | 70 | | | | | |
| CBL-500C-50 | 50.3 | 100 | 8 | 75 | M10 | 11 | | | |
| CBL-500C-55 | 55.3 | 110 | | 85 | | | | | |
| CBL-500C-60 | 60.3 | 120 | | 90 | | | | | |
| CBL-500C-65 | 65.3 | 125 | | 95 | | | | | |
| CBL-500C-70 | 70.3 | 130 | | 100 | | | | | |
| CBL-500C-75 | 75.3 | 140 | 10 | 110 | M10 | 11 | | | |
| CBL-500C-80 | 80.3 | 150 | | 120 | | | | | |
| CBL-500C-90 | 90.5 | 170 | | 140 | | | | | |
| CBL-500C-100 | 100.5 | 190 | | 160 | | | | | |
| CBL-500C-120 | 120.5 | 200 | | 175 | | | | | |